

SD6-WEB

DC/DC Converters System of Double Input Busbar

- Cabinet Dimensions (mm) : 600x600x2000
- Color : RAL2004 / RAL7035 (foto) / RAL7032
- Capacity fo up to 6 DC/DC Converters
- DC/DC Converter pluggable in 19" Rack
- Output Power of up to 6KW
- 2 Independent Input : 125Vdc/110Vdc/48Vdc or 24Vdc
- 1 Output : 125Vdc/110Vdc/48Vdc/24Vdc or 12Vdc
- Individual Input and Output protected by Circuit Breakers
- DC Distribution by incorporated Circuit Breakers
- Local and Remote Supervision through Module "MSC-SD6"
- Web Server (SCADA) resident on "MSC-SD6"
- Graphic parameterization and Control Console on the door
- Communication via TCP/IP or Modem
- TCP/IP Interface – Optic Fiber
- Natural Cooling (Without forced ventilation)
- High Fidelity and easy replacement
- Proved structure in hostile environments
- Local and Individual Signaling by Converter by LED

- Remote Sign by Free of Potential Contacts
- Proved Life Cycle superior to 20 years in permanent mode
- Warranty of 2 to 5 Years
- CE Marking
- Made in Portugal by Fisocrom

Application

- High Voltage Transport Network Substations and Production
- Eolic Farms of High Capacity
- Hydroelectric / Thermoelectric and Combined Cycle Centrals

